

# EA-ZLK-RA-5B-144 SERIES

Energy America 5BB Half-Cell Light-Weight Double Glass Polycrystalline PERC PV Module

335W | 340W | 345W | 350W | 355W | 360W



# **Excellent Cells Efficiency**

9BB technology decreases the distance between bus bars and finger grid line which is a benefit to power increase

# **Better Weak Illumination Response**

More power output in weak light condition, such as haze, clouds, and early morning

# Anti PID

Limited power degradation caused by PID effect is guaranteed under strict testing condition for mass production

# **High Wind & Snow Resistance**

5400 Pa Snow Load | 2400 Pa Wind Load

# 30 Years Power Warranty


After 30 years our solar panel keeps at least 80% of its initial power output

### **Durable Materials**

Advanced manufacturing technology minimizes chances of micro-cracks resulting from impact or heat

### Ruggedized Construction

Built to withstand real-world conditions. Rated for heavy snow loads up to 5400 Pa and wind loads up to 2400 Pa
































Since 2013, EA products have been constantly contributing clean energy to our planet. As a globally recognized innovator, our success in production, technological development, quality control, and product performance distinguishes EA as one of the most reliable solar companies in the world. Designed in the United States for global applications, reliability content and industry protection leading at 30 years product and power warranty. Compatible countries include Northern & Latin America, Asia South Pacific, Middle East, African Region, and Indian Territory.


# EA-ZLK-RA-5B-144 SERIES

Energy America 5BB Half-Cell Light-Weight Double Glass Polycrystalline PERC PV Module






Front View




**Back View** 



### **I-V CURVES OF** PV MODULE (350W)



### P-V CURVES OF PV MODULE (350W)



# **ELECTRICAL CHARACTERISTICS | STC\***

Nominal Power Watt Pmax (W)**	335	340	345	350	355	360
Power Output Tolerance Pmax (%)	0~+3	0~+3	0~+3	0~+3	0~+3	0~+3
Maximum Power Voltage Vmp (V)	37.90	38.10	38.30	38.50	38.70	38.90
Maximum Power Current Imp (A)	8.84	8.93	9.01	9.10	9.18	9.26
Open Circuit Voltage Voc (V)	46.60	46.80	47.00	47.20	47.40	47.60
Short Circuit Current Isc (A)	9.16	9.22	9.28	9.37	9.45	9.53
Module Efficiency (%)	16.89	17.14	17.39	17.64	17.89	18.15

<sup>\*</sup>STC (Standard Test Condition): Irradiance 1000W/m², Module Temperature 25°, AM 1.5 | \*\* Measuring tolerance: ±3%

# **ELECTRICAL CHARACTERISTICS | NMOT\***

Maximum Power Pmax (Wp)	248.30	252.60	256.40	260.30	264.00	267.70
Maximum Power Voltage Vmpp (V)	35.50	35.80	36.10	36.30	36.50	36.70
Maximum Power Current Imp (A)	6.99	7.05	7.10	7.17	7.23	7.30
Open Circuit Voltage Voc (V)	43.00	43.20	43.40	43.40	43.50	43.90
Short Circuit Current Isc (A)	7.42	7.46	7.51	7.59	7.65	7.72

<sup>\*</sup>NMOT(Nominal module operating temperature):Irradiance 800W/m²,Ambient Temperature 20°, AM 1.5, Wind Speed 1m/s

### **MECHANICAL DATA**

Solar Cells **POLY** Cells Orientation 144 (6×24)

Module Dimension 2000×992×30 mm (With Frame)

Weight

Glass 2.0 mm+2.0 mm, High Transmission, AR Coated Heat Strengthened Glass

Junction Box IP 68, 3 diodes Cables 4 mm<sup>2</sup>, 350 mm MC4-compatible Connectors

# **TEMPERATURE RATING**

NMOT	45°C±2°C
Temperature Coefficient of Pmax	-0.39%/°C
Temperature Coefficient of Voc	-0.31%/°C
Temperature Coefficient of Isc	0.06%/°C

### **WORKING CONDITIONS**

Maximum System Voltage	1500 V DC
Operating Temperature	-40°C~+85°C
Maximum Series Fuse	15 Δ

Maxmum Load (snow/wind) 5400 Pa / 2400 Pa

# PACKAGING CONFIGURATION

Piece/Box	36
Piece/Container (40'HQ)	792
Piece/Container (with additional small package)	/

Please read safety and installation instructions before using this product. Subject to change without prior notice.

<sup>\*</sup>Do not connect Fuse in Combiner Box with two or more strings in parallel connection \*Remark:Electrical data in this catalog do not refer to a singel module and they are not part of the offer.They only serve focr omparison among different module types